

Miniature fuse-links 5x20

Low breaking capacity 5SF Fast acting 250VAC

MINIATURE FUSES

5X20MM



STANDARDS

- Complying with IEC-127-2 Standard Sheet 2



Miniature fuse-links 5x20

Low breaking capacity 5SF Fast acting 250VAC

PRODUCT RANGE

250VAC from 0.080 to 20A #1#

Catalog number	Item number	Rated voltage AC (IEC)	Rated current I _n	Rated breaking capacity AC	Power dissipation at I _n	max. voltage drop	Weight
MI5SF25V8	W090524	250 V	8 A	80 A	3.3 W	0.08 V	1.2 g
MI5SF25V10	X090525	250 V	10 A	100 A	4.37 W	0.07 V	1.2 g
MI5SF25V16	X233447	250 V	16 A	-	-	-	1.2 g
MI5SF25V20	Y233448	250 V	20 A	-	-	-	1.2 g
MI5SF25V12.5	W233446	250 V	12.5 A	-	-	-	1.2 g
MI5SF25V0.08	Z090504	250 V	0.08 A	35 A	0.39 W	0.93 V	1.2 g
MI5SF25V0.1	A090505	250 V	0.1 A	35 A	0.44 W	0.84 V	1.2 g
MI5SF25V0.125	B090506	250 V	0.125 A	35 A	0.5 W	0.76 V	1.2 g
MI5SF25V0.16	C090507	250 V	0.16 A	35 A	0.57 W	0.68 V	1.2 g
MI5SF25V0.20	D090508	250 V	0.2 A	35 A	0.64 W	0.62 V	1.2 g
MI5SF25V0.25	E090509	250 V	0.25 A	35 A	0.73 W	0.56 V	1.2 g
MI5SF25V0.315	F090510	250 V	0.315 A	35 A	0.83 W	0.5 V	1.2 g
MI5SF25V0.40	G090511	250 V	0.4 A	35 A	0.94 W	0.45 V	1.2 g
MI5SF25V0.50	H090512	250 V	0.5 A	35 A	0.12 W	0.14 V	1.2 g
MI5SF25V0.63	J090513	250 V	0.63 A	35 A	0.15 W	0.13 V	1.2 g
MI5SF25V0.80	K090514	250 V	0.8 A	35 A	0.2 W	0.13 V	1.2 g
MI5SF25V1	L090515	250 V	1 A	35 A	0.27 W	0.12 V	1.2 g
MI5SF25V1.25	M090516	250 V	1.25 A	35 A	0.35 W	0.11 V	1.2 g
MI5SF25V1.6	N090517	250 V	1.6 A	35 A	0.47 W	0.11 V	1.2 g
MI5SF25V2	P090518	250 V	2 A	35 A	0.62 W	0.1 V	1.2 g
MI5SF25V2.5	Q090519	250 V	2.5 A	35 A	0.82 W	0.1 V	1.2 g
MI5SF25V3.15	R090520	250 V	3.15 A	35 A	1.08 W	0.09 V	1.2 g
MI5SF25V4	S090521	250 V	4 A	40 A	1.43 W	0.09 V	1.2 g
MI5SF25V5	T090522	250 V	5 A	50 A	1.89 W	0.08 V	1.2 g
MI5SF25V6.3	V090523	250 V	6.3 A	63 A	2.5 W	0.08 V	1.2 g

RMS value of prospective current (A) +/-10%

TIME CURRENT CHARACTERISTIC CURVES

Pre-arcing time (s)

MERSEN reserves the right to change, update or correct, without notice, any information contained in this datasheet.