

Miniature fuse-links 5x20

High breaking capacity 5HF Fast acting 250VAC

MINIATURE FUSES

5X20MM



STANDARDS

- Complying with IEC-127-2 Standard Sheet 1



Miniature fuse-links 5x20

High breaking capacity 5HF Fast acting 250VAC

PRODUCT RANGE

250VAC from 0.1 to 20A #1#

Catalog number	Item number	Rated voltage AC (IEC)	Rated current I_n	Rated breaking capacity AC	Power dissipation at I_n	max. voltage drop	Weight
MI5HF25V8	J085407	250 V	-	1500 A	3.1 W	0.106 V	1.2 g
MI5HF25V0.8	X095562	250 V	-	1500 A	0.58 W	0.2 V	1.2 g
MI5HF25V0.63	W095561	250 V	-	1500 A	1.35 W	0.41 V	1.2 g
MI5HF25V20	J210343	250 V	-	1500 A	-	-	1.2 g
MI5HF25V16	H210342	250 V	-	1500 A	-	-	1.2 g
MI5HF25V12	G210341	250 V	-	1500 A	-	-	1.2 g
MI5HF25V10	K085408	250 V	-	1500 A	3.7 W	0.1 V	1.2 g
MI5HF25V0.5	V095560	250 V	-	1500 A	1.11 W	0.43 V	1.2 g
MI5HF25V0.16	J095550	250 V	-	1500 A	0.43 W	0.52 V	1.2 g
MI5HF25V0.2	Q095556	250 V	-	1500 A	0.52 W	0.5 V	1.2 g
MI5HF25V0.1	G095548	250 V	-	1500 A	0.3 W	0.56 V	1.2 g
MI5HF25V0.125	H095549	250 V	-	1500 A	0.36 W	0.54 V	1.2 g
MI5HF25V0.315	S095558	250 V	-	1500 A	0.76 W	0.46 V	1.2 g
MI5HF25V0.4	T095559	250 V	-	1500 A	0.92 W	0.44 V	1.2 g
MI5HF25V0.25	R095557	250 V	-	1500 A	0.63 W	0.48 V	1.2 g
MI5HF25V1	Y095563	250 V	1 A	1500 A	0.69 W	0.18 V	1.2 g
MI5HF25V1.25	C095567	250 V	1.25 A	1500 A	0.81 W	0.17 V	1.2 g
MI5HF25V1.6	D095568	250 V	1.6 A	1500 A	0.96 W	0.16 V	1.2 g
MI5HF25V2	E095569	250 V	2 A	1500 A	1.1 W	0.15 V	1.2 g
MI5HF25V2.5	F095570	250 V	2.5 A	1500 A	1.3 W	0.14 V	1.2 g
MI5HF25V3.15	G095571	250 V	3.15 A	1500 A	1.6 W	0.14 V	1.2 g
MI5HF25V4	H095572	250 V	4 A	1500 A	1.9 W	0.13 V	1.2 g
MI5HF25V5	J095573	250 V	5 A	1500 A	2.2 W	0.12 V	1.2 g
MI5HF25V6.3	K095574	250 V	6.3 A	1500 A	2.7 W	0.113 V	1.2 g

RMS value of prospective current (A) +/-10%

TIME CURRENT CHARACTERISTIC CURVES

Pre-arcing time (s)

MERSEN reserves the right to change, update or correct, without notice, any information contained in this datasheet.