

Flexible combination of trigger handle scan and multifunctional smartphone for reliable data recording.

The mobile multifunctional set combines a wide range of functions and possible uses of several devices in one.

The **IS-TH1** enables the quick and easy scanning of any 1D or 2D barcodes at close range or at distances of more than 15 meters.





IS-TH1xx.1



ATEX approval: Ex Zone 1/21 II 2G Ex ib op is IIC T4 Gb II 2D Ex ib op is IIIC T135°C Db



IECEx approval: Ex Zone 1/21 Ex ib op is IIC T4 Gb Ex ib op is IIIC T135°C Db



NEC500 applied for Class I Division 1, Groups A, B, C, D, T4 Class II Division 1, Groups E, F, G, T135°C Class III Division 1

TECHNICAL SPEZIFICATION

Weight MR = 380 g | ER = 400 g (without IS530)

Size 200 x 125 x 82 mm

Indication function Loudspeaker | Vibration | LED-Display

Power supply Over IS530 | this can be loaded in the handle

Communication Over the multi functional ISM interface of the IS530

Protection MIL-STD 810G | IP68

SCAN TYPES

IS-TH1MR.1 (mid range) with Zebra SE4750 MR | up to 6 m

IS-TH1ER.1 (extended range) with Zebra SE4850 ER | over 15 m



(IS530.1)



Android[™] 10



4.5" Gorilla Glass® 3. generation, resolution 854 x 480 pixel



GSM 850/900/1800/ 1900 MHz WCDMA: UMTS B1/2/4/5/8 LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/ 26/28A/28B/29/30/66 LTE-TDD: B38/B39/B40/B41 TD-SCDMA: B34/B39



3600 mAh battery. replaceable, 3,8 V; 13,68 Wh

Qualcomm Snapdragon

Kryo Gold-Quad cores

64 GB internal memory

SDM660 Octa-Core

2.2 GHz



Bluetooth® 5



Krvo Silver-Ouad cores 1.8 GHz 4 GB RAM



2,4 GHz + 5 GHz: IEEE 802.11a/ b/g/n/ac/e/k/r/h with hotspot for max. 8 connections

The complete description you will find on our homepage: www.isafe-mobile.com

) i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. All other trademarks and copyrights are the properties of their respective owners.) © 2021 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1040MD01REV08_EN_06.2021