i.safe MOBILE



ZONE 2/22 CL I / DIV 2

IS930.2

The IS930.2 is the tablet for use in ATEX Zones 2/22 and CLI/Div2. The 8" tablet is highly robust, powerful and offers many technical advantages: 8.400 mAh battery, Qualcomm Snapdragon SDM 660 processor, NFC, Android™ 9.

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories. Is is afe MOBILE and is afe MOBILE logo are registered trademarks of is afe MOBILE GmbH. Android is a trademark of Google LLC. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. Bluetooth's is a registered trademark of Bluetooth SIG, Inc. worldwide. Wi-Fi's is a registered trademark of the Wi-Fi Alliance. All other trademarks and copyrights are the properties of their respective owners. Image: 200 by is afe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1041MD01REV04_EN 0.8.2020.





TECHNICAL FEATURES



ATEX approved: EX-Zone 2/22 **II 3G Ex ic IIC T4 Gc IP64** Dc IP6X



IECEx approved: Ex-Zone 2/22 Ex ic IIC T4 Gc IP6X Ex ic IIIC T135°C Dc IP6X



NEC500 approved: Class I, II, III Division 2 Groups ABCDFG, T4



Android 9



2,4GHz + 5GHz: IEEE 802.11a/b/g/n/ac/e/k/r/h with max. 8 connections hotspot



GSM 850/900/1800/ 1900 MHz WCDMA: UMTS B1/2/4/5/8 LTE-TDD: B38/B39/B40/B41 LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/ 26/28A/28B/29/30/66 TD-SCDMA: B34/B39



Bluetooth® 5

external memory

microSD up to 128 GB



size: 237 x 156 x 22 mm. weight: 890 g



Near Field Communication



Qualcomm Snapdragon SDM660 Octa-Core Kryo Gold-Quad cores 2.2GHz Krvo Silver-Ouad cores 1.8GHz 64 GB internal memory 54 GB accessible



magnetic charging port



2 cameras: 13 MP AF rear camera and 5 MP front camera



SOS-kev Loneworker protection LWP ready (third party application required, based on country specific regulations)

FURTHER FEATURES



waterproof: 1 hour up to 2 m, impervious to dust and microparticles



operation range from -20 °C to 60 °C



8" multi capacitive touchscreen with a resolution of 1200 x 1920 pixel, RugDisplay-Glass



usable with gloves



8.400 mAh battery



GPS, A-GPS, Glonass, Beidou, Galileo



Proximity, acceleration, light, barometer and magnetic sensor



Tablet with integrated battery, charger, USB-C cable, magnetic charging cable, quick start manual and safety instructions